





































■ DC output plug

◎ Standard plug: **Con1**

Con1 = 5.5x2.1x11mm	Pin Assignment
  	 "±" Outside  Inside

◎ Optional DC plug:

Tuning Fork Style		KRECO PN	A OD	B ID	C Length
 	 (Straight)	Con1	5.5	2.1	Normal set at 11mm (9.5 to 12mm available) Please specify to sales
		Con2	5.5	2.5	
	 (Right-angled)	Con3	5.5	2.1	
		Con4	5.5	2.5	
Barrel Style		KRECO P/N	A OD	B ID	C Length
 	 (Straight)	Con5	5.5	2.1	Normal set at 11mm (9.5 to 12mm available) Please specify to sales
		Con6	5.5	2.5	
	 (Right-angled)	Con7	5.5	2.1	
		Con8	5.5	2.5	
Lock Style		KRECO P/N	A OD	B ID	C Length
   Locking SWITCHCRAFT original or equivalent		Con9	5.53	2.03	9.5 to 12mm Please specify to sales
		Con10	5.53	2.54	
Min. Pin Style		KRECO P/N	A OD	B ID	C Length
   EIAJ equivalent		Con11	2.35	0.7	11.0
		Con12	4.0	1.7	11.0
		Con13	4.75	1.7	11.0

Center Pin Style	KRECO P/N	A	B	C	D	
		OD	ID	Length	Center Pin	
   <p>EIAJ equivalent</p>	Con14	5.5	3.4	11.0	1.0	
	Con15	6.5	4.4	11.0	1.4	
	Con16	7.4	5.1	11.0	0.6	
Min. DIN 3 Pin with Lock (male) Style	KRECO P/N	Pin Assignment				
   <p>KYCON KPPX-3P equivalent</p>	Con17	PIN	Output			
		1	+Vo			
		2	-Vo			
<th>Min. DIN 4 Pin with Lock (male) Style</th> <th>KRECO P/N</th> <th colspan="4">Pin Assignment</th>	Min. DIN 4 Pin with Lock (male) Style	KRECO P/N	Pin Assignment			
	   <p>KYCON KPPX-4P equivalent</p>	Con18	PIN	Output		
			1	+Vo		
			2	-Vo		
3			-Vo			
<th>Min. DIN 4 Pin with Lock (female) Style</th> <th>KRECO P/N</th> <th colspan="4">Pin Assignment</th>	Min. DIN 4 Pin with Lock (female) Style	KRECO P/N	Pin Assignment			
	   <p>KYCON KPJX-CM-4S equivalent</p>	Con19	PIN	Output		
			1	+Vo		
			2	-Vo		
3			-Vo			
<th>DIN 5 Pin (male) Style</th> <th>KRECO P/N</th> <th colspan="4">Pin Assignment</th>	DIN 5 Pin (male) Style	KRECO P/N	Pin Assignment			
	  	Con20	PIN	Output		
			1	-Vo		
			2	-Vo		
			3	+Vo		
4			-Vo			
<th>Stripped and tinned leads Style</th> <th>KRECO P/N</th> <th colspan="4">Pin Assignment</th>	Stripped and tinned leads Style	KRECO P/N	Pin Assignment			
	  <p>Length of L, L1 by customer's request (standard length, L: 25 mm, L1: 5 mm)</p>	Tined5mm	PIN	Output		
1			+Vo			
		2	-Vo			
			Red or White sink			
			Black			

More Connectors:
Please email to sales@kreco.com.cn